

SRR 2150

RF Routing Switch (950-2150 MHz)



General Description:

The **SRR 2150** is a unidirectional, programmable RF switch that provides signal routing capability for broadband cable frequencies (950-2150 MHz). It is equally suitable for audio/video baseband, data, IF, or RF switching environments and is available in the following configurations: 1x8, 8x1, 1x16, or 16x1. Controllable either locally via the front panel keypad or remotely through a computer interface, the SRR 2150 greatly enhances system reliability by eliminating patch panels and repetitive mechanical connections. The design of the rear panel facilitates structured cable routing, thereby eliminating confusing tangles and bundles of cables.

Specifications:

Inputs/Outputs:	1x8, 8x1, 1x16, 16x1
Frequency:	950-2150 MHz
Impedance:	75 Ω
Max. Total Operating Input Power:	-20 dBm
Insertion Loss:	0 \pm 2 dB
Frequency Response:	\pm 3 dB
Isolation:	50 dB
Return Loss:	10 dB
RF Connectors:	Type "F", 75 Ω (BNC, SMA optional)
Local Control:	Front panel keypad with LCD display
Computer Control:	RS-232, RS422/485, or TCP/IP via customer-supplied PC
Power Requirements:	100-240 VAC, 60/50 Hz
Power Consumption:	11W
Mechanical:	1 RU (1.75"H x 19"W x 18"D)
Software:	Basic IBM-compatible operating software and system protocol included with system

